

MULTI-PURPOSE WHITE-LIGHT LED

rayLUX PRODUCTS
AT A GLANCE



WHITE-LIGHT RANGE AT A GLANCE

DIRECTIONAL



300 SERIES



200 SERIES



150 SERIES



100 SERIES



50 SERIES



25 SERIES

URBAN



UBA48 ADAPTIVE SERIES



UBA32 ADAPTIVE SERIES



UBF24 FIXED SERIES



UBF16 FIXED SERIES



UBF8 FIXED SERIES


SPECIALIST



WARRIOR



LINEAR



MODULAR



PoE

WHY RAYLUX LED?



ADAPTIVE ILLUMINATION™

Adaptive Illumination™ allows the installer to adjust the angle of the light projection from a single unit to fit the specific demands of any installation. Adjustment is quick and convenient and any angle up to 180° (depending on model) is easily selectable. Adaptive Illumination is patent pending technology available exclusively from RayLED.



ACTIVE LED LIFE CONTROL

All RayLED illuminators employ cutting edge materials science techniques to improve thermal efficiency throughout the unit and ensure consistency of LED power. The New Advanced Cool Running™ system draws heat away from the LEDs, shielding the LED from abnormal stress, and allows RayLED LED products to deliver outstanding performance and consistency of illumination throughout the operational life of the illuminator.



ENERGY SAVING

All RayLED illuminators use high efficiency LED's and advanced control methods to deliver extremely low electrical consumption. RayLED illuminators are energy saving and deliver huge savings in running costs compared to traditional bulb illuminators.



SMT LED TECHNOLOGY

The future of lighting is surface mount LED technology. Compared to standard through hole LED's, surface mount LED's are a more robust solution increasing reliability and improving product life. They are also far more efficient at the dissipation of heat allowing the LED's to run at higher power and achieve significantly improved performance.



VANDAL RESISTANT

The polycarbonate lens design protects against severe blows from crowbars, baseball bats and can even withstand successive shots from air pistols and rifles (range dependant).




Source: Sodium
Consumption: 526W



Source: RAYLUX LED
Consumption: 100W



OLD TECHNOLOGY
VS NEW TECHNOLOGY



COOL RUNNING
THERMAL
MANAGEMENT

Model shown:
Directional - RAYLUX 200



DIRECTIONAL ILLUMINATION IN ACTION:



DIRECTIONAL ILLUMINATION

High Performance White-Light directional LED illuminators provide class leading performance, long life, energy efficiency and zero maintenance. They incorporate the very latest surface mount LED's to deliver excellent optical output and outstanding reliability.


The unique Adaptive Illumination™ concept provides the flexibility to direct the angle of illumination on site to suit the required lighting specification from 10 to 180 degrees.

Each unit is fitted with Active LED Life Control to carefully control LED output, delivering consistent illumination power and a projected working life of 10 years.

RAYLUX Directional illuminators are supplied with a power supply. Control features on the power supply include adjustable power output, photocell and telemetry control.



ADAPTIVE
ILLUMINATION™



QUICK START
LIGHTING ON DEMAND

BEAM PATTERNS AVAILABLE*:

10-20 degree

30-60 degree

50-100 degree

120-180 degree

*Other angles available

APPLICATIONS

PERIMETER




SECURITY




CRITICAL
INFRASTRUCTURE



INDUSTRIAL



COMMERCIAL



ARCHITECTURAL



Model shown:
Urban - Fixed Head UBF Series



Adaptive Illumination™
versions
available

URBAN LIGHTING RANGE

With all the benefits of the directional series, the RAYLUX Urban White-Light LED series allows installers to deliver multipurpose lighting for commercial applications such as footpaths, car parks and campus lighting as well as lighting for surveillance cameras.

The RAYLUX Urban series delivers crystal clear, energy saving White-Light, providing zero-maintenance and a pleasing aesthetic look.

The RAYLUX Urban series is a full product family and is the perfect energy saving choice for applications such as campus sites, hospital grounds or any application where security and safety really matters. RAYLUX Urban can also provide lighting for site camera systems to secure the surrounding area.



ADAPTIVE ILLUMINATION™

Adaptive Illumination™ allows you to alter the horizontal light distribution on-site to suit your lighting requirement.



ADAPTIVE
ILLUMINATION™



MULTI HEAD
VERSION AVAILABLE

BEAM PATTERNS AVAILABLE:*

UBF Fixed Series:


50 x 50
120 x 120
80 x 120
120 x 80

UBA Adaptive Series:

50+ x 50
120+ x 120
80+ x 120
120+ x 80

*Other angles available


APPLICATIONS



CAMPUS



HEALTH



CAR PARKS



URBAN




PATHWAY



LOCAL AUTHORITY

Model shown:
RAYLUX WARRIOR II



WARRIOR:

ATEX and IECEx approved for all Zone 1 and Zone 2 hazardous applications.

SPECIALIST LIGHTING

CORE TECHNOLOGY FOCUS

ELECTRONICS



THERMAL



OPTICS



SOFTWARE



With over 50,000 LED illuminators installed in 50 different countries, RayLED's team of engineers and lighting designers can deliver a range of bespoke solutions and products to deliver powerful, flexible and reliable lighting for many specialist requirements.

SPECIALIST

WARRIOR




- Explosion Protected for Hazardous Areas
- ATEX & IECEx Rated
- Zone 1 and Zone 2

LINEAR



- High Power Illumination
- Linear - Perfect for Tunnels
- Flexible Design

MODULAR




- High Power Directional Illumination
- Modular - Perfect for Architecture
- Up to 31,200 lumen


PoE



- Operates from PoE
- Externally Rated
- Internal PSU/Photocell




PRISON LIGHTING



ARCHITECTURAL LIGHTING

APPLICATIONS


TUNNELS




PETROL FORECOURT



MACHINE VISION



SOLAR LIGHTING



OIL & GAS




PRISONS



FREE
SPECIALIST
DESIGN SERVICE

Model shown:
Directional - RAYLUX 200



10°, 30°, 50°,
120°, 80°/120°
or 120°/80°
Variations

Advanced
PLATINUM
SMT LED
Technology

Vandal
Resistant

Quick start
on activation

Adaptive
Illumination™

Ultra Low
Running
Costs & Zero
Maintenance

Active LED
Life Control

Even Output
Illumination

Low Voltage
Options
Available

TECHNICAL SPECIFICATIONS

RAYLUX DIRECTIONAL SERIES

Model	Consumption	Lumen Output*	Colour Temp**	CRI**	Temp	Colour	Angles	Bracket***	IP	Weight
RL300	<120W	7000	6500K	74-80+	-50 °C to +50 °C	Silver other RAL options available	Various	U-Bracket	IP66	6kg
RL200	<80W	4700	6500K	74-80+						4kg
RL150	<75W	4600	6500K	74-80+						3.5kg
RL100	<50W	3100	6500K	74-80+						3kg
RL50	<25W	1600	6500K	74-80+						1.7kg
RL25	<15W	800	6500K	74-80+						1kg

RAYLUX URBAN SERIES

Model	Consumption	Lumen Output*	Colour Temp**	CRI**	Temp	Colour	Angles	Bracket***	IP	Weight
UBA48	<80W	4700	6500K	74-80+	-50 °C to +50 °C	Silver other RAL options available	Various	Side Entry	IP66	5kg
UBA32	<50W	3100	6500K	74-80+						4kg
UBF24	<40W	2350	6500K	74-80+						3kg
UBF16	<25W	1600	6500K	74-80+						2.5kg
UBF8	<15W	800	6500K	74-80+						1.5kg

Operating Voltage: All RayLED units are supplied complete with a dedicated (Universal 100-240V AC auto sensing) current controlled PSU c/w adjustable photocell, power and telemetry input.

NOTE: Full independent photometry available on request.



WHY ADAPTIVE ILLUMINATION™?

Adaptive Illumination™ allows the installer to adjust the angle of the light projection from a single unit to fit the specific demands of any installation. Adjustment is quick and convenient and any angle up to 180 ° (depending on model) is easily selectable. Adaptive Illumination is patent pending technology available exclusively from RayLED.

* Lumen output depends upon final lens selection. Lumen output shown based on average between 10 and 50 degree angles.

** Cool White as standard - Warm White options available. CRI published reflects range between Cool and Warm White.

*** Other options available including wall and post top with a range of adapters.

TECHNICAL – BRACKETS

RAYLUX URBAN – BRACKET SOLUTIONS

All Raylux Urban products are supplied with an integrated cable managed arm. This can be used in conjunction with a range of mounting accessories or can be mounted directly to existing columns (adapters may be required).




UBF Range

UBA Version

- Tube outreach 125mm
- o/d (outside diameter) 33.7
- i/d (inside diameter) 28


BRACKET OPTIONS (URBAN SERIES)

WALL BRACKET



- Finished in Silver
- o/d (outside diameter) 42.5
- i/d (inside diameter) 34.5

TOP STUB BRACKET



- Arm o/d 42.4, i/d 36.4
- Bracket Cup o/d 88.9, i/d 80.9
- Fits 76 Spigot
- Twin Version Available

HOCKEY BRACKET




- Arm o/d 42.4, i/d 36
- Bracket Cup o/d 88.9/i/d 80.9
- Fits 76 Spigot
- Twin Version Available

ADAPTOR KIT


Various Adaptor Kit options available - contact RayLED

RAYLUX DIRECTIONAL SERIES

All Raylux 'Adaptive illumination' directional series are supplied as standard with an AI Circular bracket. This provides a large degree of flexibility of mounting options. This can be attached directly to a wall, ceiling and a range of bracket accessories including Pan and Tilt brackets (please contact for full listing)



AI Circular bracket (RL300, RL200, RL150, RL100 & RL50)




RL 25 series U-Bracket.

TECHNICAL – PSU


All Raylux products are provided complete with a dedicated current controlled PSU (Power Supply Unit), delivering outstanding performance and consistency of illumination throughout the illuminators life.*

RAYLUX URBAN SERIES

The Urban series has a slim line PSU designed to fit within most general lighting column bases (exc. UBA48).**




UBA48
160mm x 160mm x 81mm




UBA32, UBF24, UBF16, UBF8
(suitable for most column bases)
248mm x 78mm x 55mm

RAYLUX DIRECTIONAL SERIES


The Raylux directional series PSU's are designed to be mounted externally on a column, wall or internally in a feeder pillar / suitable column base.



RL25 AND RL50 SERIES
160mm x 120mm x 80mm



RL100 AND RL200 SERIES
160mm x 160mm x 81mm



RL150 AND RL300 SERIES
240mm x 160mm x 81mm

PSU STANDARD FEATURES:

- Input: Universal 100-240V AC auto-sensing
- Output: Low Voltage (~14V Current Controlled)
- -50 to +50 C
- IP67
- Telemetry (Volt Free)
- Integrated Photocell (Adjustable)
- Power Adjustable

OPTIONAL PRO PSU:

As above plus:

- 12V (1amp) DC Output
- Photocell Following Contact
- Allows Pro IQ and Pro Pulse modules to be fitted

PRO PSU PLUG IN MODULES:

PRO IQ

- Remote Illumination Adjust (Dim and Boost)
- Energy Saving Setting
- Deterrent setting
- Timer options

PRO PULSE

- Synchronization with vision technologies
- Suitable for ANPR and Machine vision purposes

* The PSU unit is designed to be positioned separately from the illuminator head, providing easy installation and access for adjustment and maintenance purposes.

** For multiple head applications a wider column base or feeder pillar may be required. The photocell is positioned on the illuminator head.



Q & A

Q WHAT DO I NEED TO CONSIDER WHEN CREATING A LIGHTING SPECIFICATION?

- A**
- What is the purpose of the light?
 - What kind of light is already around or installed?
 - How much light do I really need, and what are the long-term energy costs?

Contact RayLED for your free lighting specification document detailing key considerations and checklist items.

Q HOW MUCH DOES IT COST TO RUN A RAYLUX PRODUCT?

- A** Based on electrical consumption and maintenance costs the RL200 and UBA48 Adaptive Illumination™ system cost only £35 per year to operate. This compares to £242 for a traditional 300W mains operated halogen luminaire, and £96 for a White SON.

How much money, energy and CO₂ can I save?

Eg) Switching 10 x 300W halogen luminaires to 10 x RL200/UBA48 units saves £2,070, 9,680 kWh of power and 5 tonnes of CO₂ per year. Switching 10 x 150W White SONs to 10 x RL200/UBA48 units saves £610, 3,080 kWh of power and 2 tonnes of CO₂ per year. *

Q DO RAYLUX PRODUCTS EMIT OBTRUSIVE LIGHT?

- A** With all RAYLUX products you can direct the light precisely where it is required without wasting light or energy. The RAYLUX Urban range also has an environmental protection shield that effectively restricts upward light.

Q CAN I USE YOUR PHOTOMETRIC DATA IN LIGHTING DESIGN PACKAGES?

- A** Yes – you can request or download RAYLUX photometric files that are compatible with most proprietary lighting design packages including Relux, Dialux and Reality. However it is important to follow the guidelines when preparing a design to ensure that you gain the best advantage when using the RayLED Adaptive Illumination™ feature.

Q CAN I RUN RAYLED PRODUCTS DIRECTLY FROM MY OWN LOW VOLTAGE SOURCE?

- A** Generally no. However, low voltage versions of the PSUs are available to order. RayLED also manufacture a full range of FUSION White-Light products which run directly from 12/24V AC/DC input. Using any other power source will invalidate the product warranty and jeopardise the performance of the product.

Q CAN I ALTER THE POWER ON SCENE?

- A** Yes. All RayLED PSU's have the ability to adjust the power via a simple adjustable potentiometer. This means that if you have too much power on scene you can easily adjust the setting to match the scene; remote adjustment available.

Q CAN RAYLUX UNITS BE SWITCHED ON REMOTELY OR VIA A PIR?

- A** Yes, via a simple telemetry connection in the PSU or if required via the VMS (Video Management System) or (Building Automation Software). Additional functionality is available from the PRO Series PSU including dimming, timer and deterrent functions.

Q CAN THE RAYLED TEAM HELP WITH LIGHTING DESIGN AND SPECIFICATION?

- A** Yes. RayLED have a team of lighting designers that utilise several design software packages and are happy to work closely with you in designing and specifying the correct products for your project. RayLED also provide a free lighting survey and a comprehensive energy saving report.

*Calculations based on 4400 hours use per year at 10p kw/hr and £40 labour/maintenance costs at per unit.