

# rayMAX 25

## INFRA-RED PRODUCT RANGE

The RAYMAX series of High Performance Infra-Red LED illuminators provide class leading performance, long life and zero maintenance. They incorporate the very latest surface mount LED's to deliver excellent night-time pictures with improved optical output and outstanding reliability.

Purpose designed to provide even output illumination, RAYMAX 25 is available in a number of different fixed angle variations to handle most standard installations.


Each unit is fitted with Active LED Life Control to carefully control LED output, delivering consistent illumination power and a projected working life of 10 years.

RAYMAX illuminators are supplied with bracket and power supply. Control features on the power supply include adjustable power output, photocell and telemetry control. RAYMAX 25 is suitable for all low light installations up to 35 metres (115ft).

**RAYMAX 25 is also available with low voltage PSU.**



### INFRA-RED IN USE:



Infra-Red off



Infra-Red on

### POWERFUL

- Distances up to 35m (115ft)
- Latest LED technology
- High power - low running costs

### FLEXIBLE

- Various angles (30°, 50° or 120°)
- Fully Controllable Power Supply
- Optional Low Voltage PSU

### RELIABLE

- 10 year life
- Active LED Life Control
- Vandal resistant

### CONTROLLED

- Zero Light Pollution
- Even Output Illumination
- Semi-Covert (850nm) or Covert (940nm) Options

## APPLICATIONS





### ACTIVE LED LIFE CONTROL

All RayLED illuminators employ cutting edge materials science techniques to improve thermal efficiency throughout the unit and ensure continuity of LED power. The New Advanced Cool Running™ system draws heat away from the LEDs, shielding the LED from abnormal stress, and allows LED products to deliver outstanding performance and consistency of illumination throughout the operational life of the illuminator.



### SMT (Surface Mount Technology)

The future of lighting is surface mount LED technology. Compared to standard through hole LED's, surface mount LED's are a more robust solution increasing reliability and improving product life. They are also far more efficient at the dissipation of heat allowing the LED's to run at higher power and achieve significantly improved performance.



### VANDAL RESISTANT

The polycarbonate lens design protects against severe blows from crowbars, baseball bats and can even withstand successive shots from air pistols and rifles (range dependant).



### ENERGY SAVING

All RayLED illuminators use high efficiency LED's and advanced control methods to deliver extremely low electrical consumption. RayLED illuminators are energy saving and deliver huge savings in running costs compared to traditional bulb illuminators.



### HIGH DEFINITION LIGHTING

High Definition Lighting allows cameras to provide crystal clear, high signal images during the hours of darkness. The breakthrough in HD lighting is made possible with RayLED's high power LED technology delivering increased power on scene.

## 5 YEAR WARRANTY

All RayLED CCTV illuminators are provided with a 5 year warranty, unmatched anywhere in the CCTV lighting industry. RayLED illuminators provide guaranteed long life!

## TECHNICAL SPECIFICATIONS

**ILLUMINATOR**

*Max Distance:* up to 35m (115ft)  
*Angle:* 30, 50 or 120 degrees  
*Optics:* SMT LED's  
*Consumption:* 10W max  
*Voltage:* 13.5V current controlled  
*Weight:* 0.5kg (1.1lbs)  
*Environmental:* IP66  
*Temp Range:* -50 to +50°C (-58 to 122°F)  
*Cable Length:* 2.5m  
*Colour:* Black  
*Wavelength:* 850 or 940nm  
*Dimensions:* 75 x 100 x 54mm  
 3" x 4" x 2" approx

**BRACKETRY**  
 U Bracket and Adaptive Illumination bracket included.  
 Optional pole mount and wall mount brackets available

**POWER SUPPLY**

*Input:* Universal 100-240V AC auto-sensing  
 Low Voltage 12-24V option also available

*Output:* 10W max  
*Temperature:* -50 to +50°C (-58 to 122°F)  
*Weight:* 0.9kg (2lbs)  
*Dimensions:* 130mm x 130mm x 60mm  
 5.1" x 5.1" x 2.4" approx

**Standard PSU (included)**  
 Adjustable photocell  
 Adjustable power output for IR  
 Telemetry Control

**Optional Upgrade: PRO Series PSU**  
 PRO series PSU with optional PRO IQ and PRO Pulse plug-in modules provides user defined multi-function settings and remote control. In addition to photocell following contact and 12V DC output, PRO series features: Ecologic energy saving setting, Perma-Light consistent power setting, remote dim and boost, as well as deterrent, pulse and timer functions.

PART CODES			DISTANCES
RM25-10	RAYMAX 25, 10°	AI, 850nm + PSU	35m (115ft)
RM25-30	RAYMAX 25, 30°	AI, 850nm + PSU	20m (66ft)
RM25-50	RAYMAX 25, 50°	AI, 850nm + PSU	14m (46ft)
RM25-120	RAYMAX 25, 120°	AI, 850nm + PSU	8m (26ft)
RM25-10-C	RAYMAX 25, 10°	AI, 940nm + PSU	Contact RayLED
RM25-30-C	RAYMAX 25, 30°	AI, 940nm + PSU	Contact RayLED
RM25-50-C	RAYMAX 25, 50°	AI, 940nm + PSU	Contact RayLED
RM25-120-C	RAYMAX 25, 120°	AI, 940nm + PSU	Contact RayLED